Enviro solution.

In some applications, a cartridge filter is the very best option. And in those situations, the unique Australian made and designed Aquatight Enviro Cartridge Filters are also the very best option.

- · Perfect for pools and spas no back-wash line
- Ideal where waste water disposal is a problem
- 5 year warranty



AQUATIGHT PRODUCTS POOL PUMPS SAND FILTERS CARTRIDGE FILTERS SALT CHLORINATORS CHEMICAL CONTROLLERS SOLAR CONTROLLERS SWIM SYSTEMS SOLAR SHOWERS FILTER MEDIA LED LIGHTING



Description

The Aquatight Enviro Cartridge Filter is remarkably compact. The unique design allows for 3 output configurations, all with 1 inlet and up to 3 outlets. In all 3 configurations it provides exceptional performance in a very convenient package.


High Quality


The quality of any cartridge filter is primarily determined by the quality of its cartridge. The Enviro Cartridge Filters use one of the world's best Du Pont Reemay filter elements. The finest particles are filtered without embedding them in the element. So it not only cleans the water more completely, it also cleans itself more thoroughly and more easily than other cartridges. When it does need cleaning, the lid is simple to remove.

Reliability

The lock ring lid provides a safe and sure method of sealing the lid positively even under the high pressures created by today's pumps. Every Aquatight Enviro Filter will cope easily with high spa temperatures and while the maximum operating pressure is just 300 kpa. When sealed the automatic internal pressure release valve prevents damage to the pump and filter should the filter element ever become blocked.







| Model | Flow Rate | Filter Area mm² | Pump Size Watts (output) | Weight kg | Dim "A" mm | Dim "B" mm |
|-------|-----------|---------------------------|------------------------------------|---------------------|----------------------|---------------|
| E 50 | 225 | 475 | 550-750 | 7.0 | 465 | 345 |
| E 75 | 290 | 700 | 550-1100 | 8.0 | 465 | 345 |
| E 100 | 375 | 940 | 750-1100 | 15.5 | 665 | 345 |
| E 150 | 445 | 1400 | 750-1500 | 16.5 | 665 | 345 |
| E 200 | 490 | 1900 | 750-1500 | 24.0 | 865 | 345 |
| E 250 | 515 | 2400 | 750-1500 | 25.0 | 865 | 345 |

